

# ELECTRONIC CALIPERS

## 799 ELECTRONIC CALIPERS



### 0-40"/0-1000MM

The 799 Electronic Caliper is light, comfortable, easy-to-use, and constructed with features that have made Starrett slide calipers the machinist's first choice for many years.

The 799 offers a slim, streamlined profile, a large, clear, easy-to-read LCD display, long battery life, and function buttons for zero and inch/mm.

799 are available in 0-6", 0-8", and 0-12" sizes and the newly available extended range 24" and 40". All sizes furnished in a fitted, protective case.

### FEATURES (ALL SIZES)

- Lightweight, ergonomic design
- Inch/millimeter conversion reads .0005" or 0.01mm
- Easy access to the single, long-life battery
- Last measuring position retained when shut off
- Hardened stainless steel body for long life
- Fine adjustment thumb wheel
- Lock screw to hold the slide in position
- Resolution is .0005" (0.01mm)
- Zero at any position

799 Electronic Calipers		
Range	Cat. No.	EDP
0-6" (150mm)	799A-6/150	67410
	799A-6/150 W/SLC†	67620
0-8" (200mm)	799A-8/200	67412
	799A-8/200 W/SLC†	67413
0-12" (300mm)	799A-12/300	67621
0-24" (600mm)	799AZ-24/600	11978
0-40" (1000mm)	799AZ-40/1000	11979

Accessories and Case Information for 799 Electronic Calipers		
Description	Cat. No.	EDP
Center distance attachment*	PT26151	64440
Depth attachment for 6", 9" and 150mm calipers	PT22431	64640
3 Volt battery; CR2032	PT99492	65650
Deluxe padded case for 0-6" (150mm) calipers	723ZZ-6/722ZZ-6	57070
Finished wood case for 0-8" (200mm) calipers	950	63878
Finished wood case for 0-12" (300mm) calipers	946	56695

\* See details in this section.

†Includes redemption card for Standard Letter of Certification (SLC).

### Approximate Jaw Depths for 799 Electronic Calipers

	6" (150mm)	8" (200mm)	12" (300mm)	24" (600mm)	40" (1000mm)
Outside	1-1/2" (38mm)	2" (50.8mm)	2-1/2" (63.5mm)	4" (100mm)	6" (150mm)
Inside	5/8" (16mm)	3/4" (19mm)	23/32" (18.3mm)	11/16" (17.46mm)	11/16" (17.46mm)

### 6", 8" AND 12" CALIPERS ONLY

- Large easy-to-read LCD, .32" high characters
- Automatic shut-off after 5 minutes of nonuse
- Linear accuracy meets DIN862
- Integrated depth rod

### EXTENDED RANGE 24" AND 40" CALIPERS

- Preset and hold feature
- Minimum and maximum limits set
- I.D. jaw dimension is 0.800"/20.32mm
- LCD characters are .50" high
- Auto shut-off after 30 minutes of non-use

