

# ELECTRONIC CALIPERS

## 798 ELECTRONIC CALIPERS



0-12"/0-300MM

The 798 Electronic Caliper features a large, easy-to-read, high contrast LCD readout. It includes IP67 protection against coolants, water, chips, dust and dirt often found in machine shop environments. Its induction type linear encoder system and Inch/millimeter conversion makes Starrett precision measuring tools the right choice for any job.

798 Electronic Calipers			
Range	Description	Cat. No.	EDP
0-6" (150mm)	Caliper with output	798B-6/150	12521
	Caliper with output	798B-6/150 W/SLC	12522
	Caliper with output	798BX-6/150	12782
	Caliper without output	798A-6/150	20798
0-8" (200mm)	Caliper with output	798B-8/200	12523
	Caliper with output	798B-8/200 W/SLC	12524
	Caliper without output	798A-8/200	20799
0-12" (300mm)	Caliper with output	798B-12/300	12525
	Caliper with output	798B-12/300 W/SLC	12526
	Caliper without output	798A-12/300	20800

  

Accessories, Cables and Case Information for 798 Electronic Calipers		
Description	Cat. No.	EDP
Center distance attachment	PT26151	64440
Depth attachment	PT22431	64640
Computer interface cable to PC (USB) with driver CD	PT63388	72517
Replacement non-contact computer interface cable to PC (USB)	PT63329-1	12733
Two 3-Volt batteries, CR2032	PT99492	65650
Deluxe padded case for 0-6" (150mm) calipers	723ZZ-6/722ZZ-6	57070
Finished wood case for 0-8" (200mm) calipers	950	63878
Finished wood case for 0-12" (300mm) calipers	946	56695

\*Includes redemption card for Standard Letter of Certification (SLC).

### FEATURES

- IP67 level of protection
- Fine adjustment
- Hardened stainless steel measuring surfaces
- Large, easy-to-read, high-contrast LCD digital readout
- Induction type linear encoder system
- RS232 output
- Heavy-duty bar and slide
- Slide lock
- One 3-volt battery for over one year of normal usage
- In/mm conversion
- Zero at any position
- Auto-Off after 30 minutes
- Reactivation of display with no loss of position
- Works well with Starrett DataSure® Wireless Data Collection Systems

### Approximate Jaw Depths for 798 Electronic Calipers

	6" (150mm)	8" (200mm)	12" (300mm)
Outside	1-1/2" (38mm)	1-7/8" (47.6mm)	2-1/2" (63.5mm)
Inside	5/8" (16mm)	3/4" (19mm)	3/4" (19mm)



### IP PROTECTION

An IP number is composed of two numbers, the first referring to protection against solid objects and the second against liquids.

**First number 6:** Totally protected against dust

**Second number 7:** Protection against submersion in water under standardized conditions of pressure for 30 minutes

